

BTS-X: Bump Test Station



Completely Pneumatic, can be used in all industrial hazard areas.

Fully stainless steel construction with no electrical or battery function.

Don't leave the worksite to test your gas detector.

Can be used with any gas detection instrument. Response in seconds, ready to test immediately. One button operation for up to 2 units at a time. Usable with both large and small volume cylinders.

SPECIFICATIONS:

Max Inlet Pressure	
High-Pressure Inlet:	150BAR
High-Pressure Connection:	¼" NPT Female
Low-Pressure Inlet:	70BAR
Low-Pressure Connection:	C10 valve
No. of instruments:	Two at the same time
Usage Temperature:	-20°C to +50°C
Weight:	9.5 Kg
Flow time:	Up to 60 seconds
Flow Rate:	1.0 litres/ minute
Dimensions (HxWxD):	350mm x 450mm x 130mm
Materials	
Case:	304L Stainless Steel
Fixings:	316L Stainless Steel
Wetted Materials	
Regulators:	304L Stainless Steel
Gauge:	316L Stainless Steel
Fittings/Tube:	316L Stainless Steel
Gas Compatibility:	All gas types
Cylinder Compatibility:	112DA, 58DA, 60DA, 103DS and all high pressure specialty gas cylinders



Custom Gas Mixtures

Gas Control

Gas Generators

Leaders in Specialty Gas Solutions.

WWW.CACGAS.COM.SG

CAC@CACGAS.COM.SG