

# Flow Regulators

## for Every Gas Detection Application



**Non-Refillable/Disposable Cylinders**

**Large Volume/High Pressure Cylinders**

### Fixed Flow Regulators

0.5, 1, 2 or 10 litres/min

FF-100



FF-200



Fixed Flow Regulators are used for all types of diffusion instruments where a specific flow rate is required. Available in different flow rates the FF series is available for both disposable cylinders and large volume/high pressure cylinder mixtures. Both styles are available in either nickel plated brass or stainless steel.

### Variable Flow Regulator

4 Options available in either VAF-100 or VAF-200 series.

Available in nickel plated brass or stainless steel, both with 9 flow rates in one regulator.

0 - 5 litres/min OR 0 - 3 litres/min

VAF-100 Series



VAF-200 Series



Variable Flow Regulators are ideal for customers or service technicians who must calibrate multiple analysers with different flow rates. Simply dial the flow required on the top of the regulator. Available in nickel plated brass or stainless steel.

### On Demand Flow Regulator

0.3 - 3 litres/min

ODFR-1001



ODFR-2001



ODFR (On Demand Flow Regulator) is designed for instruments with internal pumps or docking stations with pump systems. Capable of a flow range from 0.3-3 litres/min the ODFR provides the flow required by the instrument/station. Available in nickel plated brass or stainless steel.

All flow regulators are available for high pressure/large volume cylinders.  
Select the connector which matches your cylinder valve.



FF-200



VAF-200



ODFR-2001

Splitters, available in brass or stainless steel, allow connection of two or more high pressure regulators from the same cylinder.  
Excellent for manual calibration of different types of instruments or for connecting to docking stations.



### Common Connectors



BS 3

Typically used with:  
CO<sub>2</sub> ; Air ; Nitrogen



BS 4

Typically used with:  
CO ; CH<sub>4</sub> ; (CO/CO<sub>2</sub>/CH<sub>4</sub>/O<sub>2</sub>)



BS 15

Typically used with:  
H<sub>2</sub>S ; 4GAS(H<sub>2</sub>S/CO/CH<sub>4</sub>/O<sub>2</sub>)



CGA 330



Custom Gas Mixtures

Gas Control

Gas Generators

# Leaders in Specialty Gas Solutions.