

Regulators for Non-Refillable Cylinders

Regulators for non-refillable cylinders are available in a number of different configurations including fixed flow, push button, on demand flow and variable flow models.

Each model has a variety of flow rates and are available in either nickel plated brass or stainless steel.

Regulator Series	Type	Inlets	Outlets	Body Materials	Flow Rates (L/minute)	Cylinder Type
FF-100	Fixed Flow	C10 (5/8" UNF M)	3/16" Hose Barb	Nickel Plated Brass	0.25, .3, .4, .5, 1, 2 or 10	34DA, 60DA, 65DA, 103DS, 112DA
FF-100-SS	Fixed Flow	C10 (5/8" UNF M)	3/16" Hose Barb	Stainless Steel	0.5 or 1	34DA, 60DA, 65DA, 103DS, 112DA
FF-100-SM	Fixed Flow	C10 (5/8" UNF M)	Septum	Nickel Plated Brass	1	34DA, 60DA, 65DA, 103DS, 112DA
FF-120	Fixed Flow	CGA 600	3/16" Hose Barb	Nickel Plated Brass	0.5 or 1	34DS
PBR-100	Push Button	C10 (5/8" UNF M)	3/16" Hose Barb	Nickel Plated Brass	0.5, 1, 2 or 10	34DA, 60DA, 65DA, 103DS, 112DA
ODFR-1001	On Demand Flow	C10 (5/8" UNF M)	3/16" Hose Barb	Nickel Plated Brass	0.3 – 3	34DA, 60DA, 65DA, 103DS, 112DA
ODFR-1001-SS	On Demand Flow	C10 (5/8" UNF M)	3/16" Hose Barb	Stainless Steel	0.3 – 3	34DA, 60DA, 65DA, 103DS, 112DA
VAF-103	Variable Flow	C10 (5/8" UNF M)	3/16" Hose Barb	Nickel Plated Brass	0.3, 0.5, 0.7, 0.9, 1.2, 1.5, 2, 2.5, 3	34DA, 60DA, 65DA, 103DS, 112DA
VAF-103SS	Variable Flow	C10 (5/8" UNF M)	3/16" Hose Barb	Stainless Steel	0.3, 0.5, 0.7, 0.9, 1.2, 1.5, 2, 2.5, 3	34DA, 60DA, 65DA, 103DS, 112DA
VAF-105	Variable Flow	C10 (5/8" UNF M)	3/16" Hose Barb	Nickel Plated Brass	0.5, 0.75, 1, 1.5, 2, 2.5, 3, 4, 5	34DA, 60DA, 65DA, 103DS, 112DA
VAF-105SS	Variable Flow	C10 (5/8" UNF M)	3/16" Hose Barb	Stainless Steel	0.5, 0.75, 1, 1.5, 2, 2.5, 3, 4, 5	34DA, 60DA, 65DA, 103DS, 112DA